

The perfect solution for converting digital audio media formats. This optical to coaxial converter will allow you to connect the toslink optical output from your DVD cable, game console, HDTV or satellite receiver to a coaxial digital audio input. Simply change media formats and get full digital signal sound quality.

This digital audio converter not only provides maximum sample rates of 24bit/192KHz, also maintains all surround formats, your audio signal will not be degraded or compromised in any way upon conversion.

## SPECIFICATIONS

Input: TOSLINK optical jack x 1

Output: digital SPDIF COAXIAL jack x 1

Supported sample rates: 44.1 KHz, 48 KHz, 96 KHz & 192 KHz

Power: DC 6V

Size: approx. 72mm (L) x 48mm (W) x 23mm (H)

Weight: 33 grams

## CONNECTIONS

Step 1: Power off all devices before making connections.

Step 2: Connect a toslink optical cable from the audio output source to the digital audio converter.

Step 3: Connect a digital coaxial (S/PDIF) cable from digital audio converter to the audio output device.

Step 4: Connect the AC/DC power adapter from the digital audio converter to an available AC outlet.

Step 5: Power on both the audio input device and the source.

## SYSTEM REQUIREMENTS

- Source with toslink optical digital audio output
- Audio input device with coaxial (S/PDIF) digital audio input

## PACKAGE CONTENTS

- TOSLINK Optical to Coaxial (S/PDIF) Digital Audio Converter
- AC/DC power adapter
- User Manual

