



5.25" 2 Way Active PA Speaker



CS-2470

User Manual


Box Contents

- 1 x 5.25" 2 Way Active PA Speaker
- 1 x 3m speaker wire
- 1 x 110-240V Power Supply

Basic Setup of the CS-2470

- 1) Determine the ideal location where the Patio Speakers are not exposed directly to the elements. Note: speakers typically should be placed between 8 to 12 feet apart for proper stereo separation.
- 2) The Master Patio Speaker needs to be located near an AC outlet where you can connect the Power Supply to the Master Speaker in order provide the electrical current needed for the Internal Stereo Power Amplifier and Bluetooth Receiver.
- 3) The Pairing speaker must be connected to the Master Speaker with the 30-foot Speaker Cable that is supplied with the kit. The length of the speaker cable can be cut down for an exact fit but should not be extended beyond 30 feet.

Back View



“State of the art” Bluetooth Operation Connects to any Bluetooth enabled device

Sync to bluetooth-enabled devices like smartphones and tablets

Bluetooth Range
30-50 Feet


Range may vary:
Distances, both unobstructed and obstructed, may differ depending on device you are syncing up to the CS-2470

Make sure both your Bluetooth device and the CS-2470 are turned on.

To pair two Bluetooth enabled devices, both the Bluetooth Device and the CS-2470 must be turned on and fully powered or fully charged. Bluetooth controls are typically found in the device's Setting or Connections menu. The CS-2470 will output a Bluetooth Sync code that will be received by the Bluetooth Device. Settings such as Volume, Mute, etc., will be controlled directly from your Bluetooth phone, tablet or other device.

Only one connection at a time:

The CS-2470 syncs with only one device at a time. You must disconnect the current device before Syncing to another device.



Features:

- Bluetooth® 3.0 source connectivity
- Compatible with A2DP standard

Specifications:

Woofer Size:	5.25"
Tweeter:	1/2" PEI Dome
Bluetooth® Range:	Up to 10m
Output:	30WRMS
Frequency Response:	80Hz - 20kHz
Impedance:	4 Ohms
Dimensions:	252(H) x 163(W) x 163(D)mm

Distributed by:
TechBrands by Electus Distribution Pty. Ltd.
320 Victoria Rd, Rydalmere
NSW 2116 Australia

Ph: 1300 738 555
Int'l: +61 2 8832 3200
Fax: 1300 738 500

www.techbrands.com

Made in China