



Material Designation: **FM090**

Product Description: Acetal 'polyoxymethylene' (POM), furnished as pellets.

| Color | Min. Thick. (mm) | Flame Class | HWI | HAI | RTI Elec | RTI Imp | RTI Str | IEC GWIT | IEC GWFI |
|---------------|------------------|-------------|----------------|-----|----------------|---------|------------------|----------|----------|
| ALL | 0.80 | HB | 5 | 0 | 110 | 90 | 90 | - | - |
| | 3.0 | HB | 3 | 0 | 110 | 90 | 100 | - | - |
| CTI: 0 | | | HVTR: 0 | | D495: 5 | | IEC BP: - | | |

Report Date: / /

Underwriters Laboratories Inc®

273341001

UL94 small-scale test data does not pertain to building materials, furnishings and related contents. UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in components and parts of end-product devices and appliances, where the acceptability of the combination is determined by ULI.

©Halogen Free
©ROHS compliant

| | | | | | | | |
|---|--|--|-------------------------------------|--|---|--|----------------------|
| TOLERANCE: L ≤ 10 ±0.2 10 < L ≤ 30 ±0.3 30 < L ≤ 50 ±0.5 50 < L ≤ 100 ±0.7 100 < L ≤ 250 ±1.2 ABOVE 250 ±1.5 | | | UNIT SCALE mm / | | PART NAME: 六角型間隔柱 SPACER SUPPORT | | VERSION 1A |
| MATERIAL: POM or EQUIVALENT COLOR: NATURAL | | | | | PART NO: HP0824 HP0825 | | |
| | | | | | SHEET 1 OF 1 | | |