



QMF22 Component - Plastics

Wednesday, January 06, 1999

E173318

FORMOSA PLASTICS CORP
ROOM 061 4TH FL 201 TUNG HWA N RD TAIPEI TAIWAN

Material Designation: **FM090**

Product Description: Acetal 'Polyoxymethylene' (POM), furnished as pellets.

Color	Min. Thick. (mm)	Flame Class	HWI	HAI	RTI Elec	RTI Imp	RTI Str	IEC GWIT	IEC GWFI
ALL	0.80	HB	5	0	110	90	90	-	-
	3.0	HB	3	0	110	90	100	-	-
CTI: 0			HVTR: 0		D495: 5		IEC BP: -		

Report Date: ___/___/___

Underwriters Laboratories Inc®

273341001

UL94 small-scale test data does not pertain to building materials, furnishings and related contents. UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in components and parts of end-product devices and appliances, where the acceptability of the combination is determined by UL.

©Halogen Free

©ROHS compliant

TOLERANCE: L ≤ 10 ±0.2 10 < L ≤ 30 ±0.3 30 < L ≤ 50 ±0.5 50 < L ≤ 100 ±0.7 100 < L ≤ 250 ±1.2 ABOVE 250 ±1.5					PART NAME: 六角型間隔柱 SPACER SUPPORT		VERSION 1A
MATERIAL: POM or EQUIVALENT COLOR: NATURAL	UNIT mm						

SHEET 1 OF 1