


3A Dual USB Type-C & A Car Cigarette Lighter Adaptor User Manual

MP-3672

Connection Diagram:



Operation:

- Before use, check your USB device's input voltage and this USB car charger's output voltage to make sure
 the voltage matches. Make sure the total current does not exceed the rated output current of this USB
 charger.
- 2. Connect your USB device and the USB port of this charger with a suitable charging cable according to the type of device.

(To ensure complete safety and best performance, we strongly recommend using the original charging cable of your device)

- 3. Plug the cigarette lighter plug into the 12-24V car cigarette lighter socket and the LED power indicator will turn on.
- 4. This intelligent USB car charger will detect the best charging mode and start charging your device automatically.
- 5. Your USB device should indicate it is now in charging mode.
- Please unplug this charger from car cigarette lighter socket when not in use.

Safety Instructions:

- 1. Do not short circuit the output terminals.
- 2. Ensure correct voltage is used as continuous excessive voltage could damage your equipment.
- 3. Do not try to use this power supply with appliance requiring more than 3000mA.
- 4. Do not attempt to open this unit.
- 5. Remove from car cigarette lighter socket when not in use.
- 6. Always turn off your digital device before you connect/disconnect from the USB charger.
- $_{\mbox{\scriptsize 7.}}$ Please do start the car engine first then plug in the USB charger.

Specifications:

Voltage Input: 10-30VDC Voltage Output: 5VDC

Current Output: 3A Type-C (Max)

2.4A Type-A (Max)

3A Shared (Max Across 2 Ports)

Protection: Short Circuit, Overload Dimensions: 50(L) x 28(Dia)mm

Distributed by:
TechBrands by Electus Distribution Pty, Ltd.
320 Victoria Rd, Rydalmere NSW 2116 Australia
Ph: 1300 738 5555
Int1: -61 2 8832 3200
Fax: 1300 738 500
www.techbrands.com
Made in China