





# SPECIALIST Safety Data Sheet

1 – Product Identifier & Identity for the Chemical					
Manufacturer: WD-40 Company Australia		Product Name: WD-40 Specialist Air Duster			
	Pty Ltd				
Address:	41 Rawson Street	Chemical Name: 1,1-Difluoroethane			
	(Level 2, Suite 23)				
	Epping	Product Use: To keep workshops, vehicles,			
	NSW, 2121, Australia	electronics or households clear of dust and			
Telephone:	1011, 2121, / aotraina	other materials.			
	+61 2 0868 2200				
Information: +61 2 9868 2200		Restriction on Use: None Identified			
Emergency only: 1800 862 115		Restriction on ose. None identified			
Deieene Information Control		SDS Data Of Branarations 1 October 2020			
Poisons Information Centre:		SDS Date Of Preparation: 1 October 2020			
Australia: 13 11 26		This CDC applies to write and (a), 24020			
New Zealand: 0800 764 766		This SDS applies to unit code(s): 21028			
New Zealand Contact Details:					
Name:	Eproducts New Zealand				
	Limited				
Address:	7D Orbit Drive				
	Albany New Zealand				
Telephone:					
Information: 09 916 6750					
Emergency only: 0800 425 459					
	-				

# 2 – Hazards Identification

# Classification of the Hazardous Chemical (in accordance with WHS Regulation)

Health	Environmental	Physical
Not Hazardous	Not Hazardous	Aerosol Category 1

# Label Elements



**Danger!** H222 Extremely flammable aerosol. H229 Pressurized container: may burst if heated.

# Prevention

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

# Storage

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Other Hazards that do not Result in Classification: None known.

3 - Composition/information on ingredients						
Ingredient	CAS #	Weight Percent	Substance			
Ū.		5	Classification			
1,1- Difluoroethane	75-37-6	>60%	Flam. Gas Cat 1 (H220) Press. Gas (H280)			

### 3 - Composition/Information on Ingredients

See Section 16 for full text of GHS Classification and H phrases

# 4 – First Aid Measures

**Ingestion (Swallowed):** Rinse out mouth and give sips of water. Do not induce vomiting unless directed to do so by medical personnel. Call a Poisons Information Center (phone 13 11 26 from anywhere in Australia or 0800 764 766 in New Zealand).

**Eye Contact:** Flush thoroughly with water. Remove contact lenses if present after the first 5 minutes and continue flushing for several more minutes. Get medical attention if irritation persists. **Skin Contact:** No first aid should be required. If irritation or frostbite develops, warm areas gradually with warm water and get medical attention if there is evidence of frostbite or tissue damage. Do not rub affected area. If irritation or symptoms persists, get medical attention. **Inhalation (Breathing):** If irritation develops, discontinue use and move to fresh air. Get medical attention attention if irritation persists.

**Most Important Symptoms:** May cause mild eye irritation. Spray will cool rapidly and may cause frostbite or cold burns if in contact with skin. May cause skin dryness on prolonged contact. Inhalation may cause drowsiness, dizziness and other nervous system effects.

Indication of Immediate Medical Attention and Special Treatment, if Needed: Immediate medical attention is not required.

# 5 – Fire Fighting Measures

Suitable Extinguishing Media: Use water spray, water fog, dry chemical, carbon dioxide. Specific Hazards Arising from the Chemical: Extremely flammable aerosol. Contents under pressure. Keep away from ignition source and open fire. Exposure of containers to extreme heat and flames can cause them to rupture often with violent force. Vapors can cause a flash fire. Vapors are heavier than air and may travel along surfaces to remote ignition sources and flash back. A vapor and air mixture can create an explosion hazard in confined spaces. Thermal decomposition will release hydrogen fluoride, carbon monoxide and phosgene. Special Protective Equipment and Precautions for Fire-Fighters: Firefighters should always wear positive pressure self-contained breathing apparatus and full protective clothing. Use shielding to protect against bursting containers. Cool fire-exposed containers with water.

# 6 – Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures: Eliminate all sources of ignition and ventilate area. Wear appropriate protective clothing (see Section 8). Environmental Precautions: Report spills to authorities as required.

**Methods and Materials for Containment/Cleanup:** Leaking cans should be placed in a plastic bag or open pail until the pressure has dissipated. Contain and collect liquid with an inert absorbent and place in a container for disposal. Clean spill area thoroughly.

# 7 – Handling and Storage

**Precautions for Safe Handling:** Avoid contact with eyes and skin. Avoid breathing vapors or aerosols. <u>Intentional misuse by deliberately concentrating vapors and inhaling can be harmful or fatal.</u> Use only with adequate ventilation. Keep away from heat, sparks, pilot lights, hot surfaces and open flames. Unplug electrical tools, motors and appliances before spraying or bringing the can near any source of electricity. Electricity can burn a hole in the can and cause contents to burst into flames. To avoid serious burn injury, do not let the can touch battery terminals, electrical connections on motors or appliances or any other source of electricity. Wash thoroughly

with soap and water after handling. Keep containers closed when not in use. Keep out of the reach of children. Do not puncture, crush or incinerate containers, even when empty. Conditions for Safe Storage, including any incompatibilities: Store in a cool, well-ventilated area, away from oxidizers and other incompatible materials. Protect from physical damage. Do not store in direct sunlight, near open flames or above temperatures greater than 50°C.

### 8 – Exposure Controls /Personal Protection

Chemical	Occupational Exposure Limits	Biological Limit Value
1,1 Difluoroethane	1000 ppm TWA AIHA WEEL	None Established

# The Following Controls are Recommended for Normal Consumer Use of this Product Appropriate Engineering Controls: Use in a well-ventilated area.

#### **Personal Protection:**

Eye Protection: Avoid eye contact. Always spray product away from your face. Skin Protection: No special protection is required for normal use. For sensitive skin or prolonged use, wear rubber gloves.

Respiratory Protection: None needed for normal use with adequate ventilation.

# For Bulk Processing or Workplace Use the Following Controls are Recommended Appropriate Engineering Controls: Use adequate general and local exhaust ventilation to maintain exposure levels below that occupational exposure limits.

### **Personal Protection:**

Eye Protection: Safety goggles recommended where eye contact is possible.

Skin Protection: Wear chemical resistant gloves if needed to avoid prolonged skin contact. **Respiratory Protection:** None required if ventilation is adequate. If the occupational exposure limits are exceeded, wear an approved respirator. Respirator selection and use should be based on contaminant type, form and concentration. Follow applicable regulations and good Industrial Hygiene practice.

Work/Hygiene Practices: Eye wash facilities should be available. Wash hands after handling. Other Protective Equipment: None required.

#### Partition Coefficient Appearance and Odor: Clear, colorless gas Not determined in an aerosol can with of n-octanol/water: slight ethereal odor Odor Threshold: Not determined Auto-ignition 849.2°F (454°C) temperature: pH: Not applicable Decomposition Not determined Temperature: -178.6°F (-117°C) Viscosity: Melting/Freezing Point: Not determined Boiling Point / Range: -13°F (-25°C) Specific Heat Value: Not determined Flash Point: <-58°F (<-50°C) Particle Size: Not applicable Not determined VOC: 0% **Evaporation Rate** (Butyl Acetate = 1): Flammability (solid, gas): 100% Not applicable Percent Volatile: Flammable Limits: LEL: 3.9% Saturated Vapor Not determined UEL: 16.9% Concentration: Vapor Pressure: 87 psia at 77°F Release of invisible Yes (25°C) flammable vapors and gases: Vapor Density (air = 1): 2.4 at 77°F (25°C) **Aerosol Protection** 1 Level (NFPA 30B): Relative Density (Water = 0.90 g/cc at 77°F Solubility: Partly miscible (25°C) 1):

#### 9 – Physical and Chemical Properties

#### 10 – Stability and Reactivity

Reactivity: Non-reactive

Chemical Stability: Stable under normal storage conditions.

Possibility of Hazardous Reactions: Polymerization will not occur.

Conditions to Avoid: Avoid extreme heat, flames and other sources of ignition.

**Incompatible Materials:** Strong oxidants, epoxides, reducing agents, alkali or alkaline earth metals- powdered Aluminum, Zinc, etc.

Hazardous Decomposition Products: Hydrogen fluoride, carbon monoxide and phosgene.

# 11 – Toxicological Information

# Health Hazards:

**Ingestion:** Swallowing is an unlikely route of exposure for an aerosol product. Swallowing may cause gastrointestinal irritation, nausea, vomiting, diarrhea, dizziness, drowsiness and other central nervous system effects.

**Eye Contact:** Direct contact with eyes may cause mild irritation with redness and tearing. **Skin Contact:** Contact with aerosol can cause frostbite. Prolonged and/or repeated contact may produce dryness.

**Inhalation:** High concentrations may cause nasal and respiratory irritation and central nervous system effects such as headache, dizziness and nausea. Intentional abuse may be harmful or fatal.

**Chronic Exposure:** Repeated inhalation of high levels of 1,1- Difluoroethane can cause increased urinary fluoride, reduced kidney weight, and reversible kidney changes. Based on an independent peer review the revisable kidney changes are considered artifacts of the tissue and slide processing and not a compound related effect.

**Medical Conditions Aggravated by Exposure:** Preexisting respiratory conditions may be aggravated by exposure.

# Acute Toxicity Values:

1,1- Difluoroethane: Inhalation rat LC50: 383,000 ppm /4hr.

Skin Corrosion/Irritation: No data available for mixture. This product is not expected to cause skin irritation.

**Serious Eye Damage/Irritation:** No data available for mixture. This product is not expected to cause eye irritation.

Respiratory or Skin Sensitization: This product is not expected to cause sensitization.

Germ Cell Mutagenicity: None of the components have been found to be mutagenic.

**Carcinogenicity:** None of the components are listed as a carcinogen or suspected carcinogen by IARC, NTP, ACGIH, US OSHA or the EU CLP.

**Reproductive Toxicity:** None of the components are known to cause adverse reproductive effects.

Specific Target Organ Toxicity:

Single Exposure: No data available.

Repeated Exposure: No data available.

**Aspiration Hazard:** Based on the viscosity test data, this product is not expected to present an aspiration hazard.

# 12 – Ecological Information

Ecotoxicity: No data is currently available. Persistence and Degradability: No data available. Bioaccumulative Potential: No data available. Mobility in Soil: No data available. Other Adverse Effects: None Known

# 13 - Disposal Considerations

**Safe Handling and Disposal Method:** Aerosol containers should not be punctured, compacted in home trash compactors or incinerated.

**Disposal of Contaminated Packaging:** Empty containers may be disposed of through normal waste management options.

**Environmental Regulations:** Dispose of all waste product, absorbents, and other materials in accordance with applicable Federal, state and local regulations.

#### 14 – Transportation Information

IMDG Shipping Name: Aerosols IMDG Hazard Class: 2.1 UN Number: UN1950

IATA Shipping Name: Aerosols, Flammable IATA Hazard Class: 2.1 UN Number: UN1950

ADG Shipping Name: Aerosols ADG Hazard Class: 2.1 UN Number: UN1950 Hazchem (Emergency Action) Code: 2YE

**Special Precautions for User:** WD-40 does not test aerosol cans to assure that they meet the pressure and other requirements for transport by air. We do not recommend that our aerosol products be transported by air.

### 15 – Regulatory Information

Montreal Protocol (Ozone Depleting Substances): None present The Stockholm Convention (Persistent Organic Pollutants): None present The Rotterdam Convention (Prior Informed Consent): Not applicable Basel Convention: Not applicable International Convention for the Prevention of Pollution from Ships (MARPOL): None present

International Convention for the Prevention of Pollution from Ships (MARPOL): None present Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP): None present

Australian Inventory of Chemical Substances: All of the components of this product are listed on the AICS inventory.

# New Zealand:

HSNO Approval Number: HSR002515

Considered a Hazardous Substance according to the criteria of the New Zealand Hazardous Substances New Organisms legislation. Classified as Dangerous Good for transport purposes.

HSNO Hazard Classes: 2.1.2A

New Zealand Inventory: All the ingredients comply with the HSNO regulations.

#### 16 – Other Information

REVISION DATE: 1 October 2020

SUPERSEDES: 13 May 2020

Prepared By: Industrial Health & Safety Consultants, Inc.

Full Text of GHS Classification and H Phrases from Section 3: Flam. Gas Cat 1 Flammable Gas Category 1 Press. Gas Gas under Pressure H220 Extremely flammable gas H280 Contains gas under pressure; may explode if heated. List of Abbreviations or Acronyms: ACGIH American Conference of Industrial Hygienists ADG Australian Dangerous Goods AICS Australian Inventory of Chemical Substances AU Australia **EC Effective Concentration** EU European Union GHS Globally Harmonized System of Classification and Labelling of Chemicals HSNO Hazardous Substances and New Organisms IARC International Agency of Research on Cancer IATA International Air Transport Association IMDG International Maritime Dangerous Goods LC Lethal Concentration LD Lethal Dosage LEL Lower Explosive Limit NTP National Toxicology Program **OEL Occupational Exposure Limits** US OSHA United States Occupational Safety and Health Administration PEL Permissible Exposure Limit SDS Safety Data Sheet STEL Short Term Exposure Limit TWA Time-Weighted Average **UEL Upper Explosive Limit VOC Volatile Organic Compounds** WHS Work Health and Safety

SIGNATURE: Inez Kowalski TITLE Regulatory Affairs Department

This SDS complies with Australian guidelines for SDS. The foregoing information has been compiled from sources believed to be accurate but is not warranted to be. Recipients are advised to confirm in advance of need that data is correct. Standards change without notice. It is the responsibility of the recipient to insure that their personnel have been notified of any changes which may affect them. The data provided on this SDS are not meant to be used as specifications, only as guideline information as to the safe use of this product. User should refer to applicable laws before use.

1066400/No.0184702