| Model | | WJ03T-Tuya |
|---------------|------------------------|---|
| Picture | | |
| Chipset Infos | Chipset | INGENIC T21 |
| | CPU | Single Core 1.0GHz |
| | RAM | 16KB L1 I-Cache and 16KB L1 D-cache. 64KB L2 unified cache. Capacity of 512Mbit |
| Video | Sensor Type | 1/4 Inch CMOS Sensor(F23) |
| | Pixel | 2.0mp 1080P |
| | Min. LUX | 0.1Lux |
| | Video Coding | H.264, MJPEG |
| | Code Stream | Double Stream |
| | Coding | Support CBR/VBR |
| | Lens Type | Full Glass Lens |
| Lens | Lens | Focus:2.9mm, Aparture:2.4 |
| | View Angle | 138° |
| Night Vision | Infrared Light | 4pcs infrared light, wavelength 940nm, range: 5m |
| | Day And Night | automatic switching |
| | Photosensitive | sensitivity 0.7Ω/Lux |
| | Audio Coding | ADPCM |
| Audio | 2 Way Audio | No |
| Audio | Built-In Mic | Support |
| | Built-In Speaker | No |
| Connection | Network Protocol | P2P, ONVIF2.4, TCP/IP, HTTP,TCP, UDP, SMTP, DHCP, NTP, RTSP, RTMP, MQTT |
| | Wired Connection | No |
| | Wireless Network | WIFI(IEEE 802.11b/g/n) |
| | Wireless Connection | WIFI Connection |
| | Connection | sound wave code and AP hot spot |
| | AP Hot Spot Connection | Support |
| | P2P Connection | Support |
| Alarm | Motion Detection | Support,High Sensitivity/Medium/Low three adjustable |
| | Sound Detection | Support,High Sensitivity/Medium/Low three adjustable |
| | Alarm Mail Push | Support G- Mail,Yahoo,Sina,Sohu,163,Alarm,Support FTP Upload Alarm Image,Turn On/Off The Function |
| | Alarm Message Push | Support |
| | | |

| Storage | Storage | Support 64G TF Card |
|--------------------|----------------------------|---|
| | Cloud Storage | No(Optional) |
| System Security | User Management | Administrators and visitors |
| | ID Anti-Theft | Support adding license to ID, Illegal piracy ID is invalid |
| Power | Power Supplier | DC5V/1A |
| | Battery Capacity | 800mAh |
| | Battery Working Time | 2 hours |
| | Certification | UN38.3, MSDS, Cargo Air/Sea transport condition test |
| Weight and Size | Product Size(mm) | 33(L) x 33(W) x 33(H) |
| | Color Box Size(mm) | 110 x 110 x 50mm |
| | Net Weight(g) | 36g |
| | Full Package Weight(g) | 190g |
| | Box(PCS) | 80PCs |
| | Weight(Kg) | 16Kg |
| | Dimension(mm) | 450*455.5*240mm |
| Physical | Working Humidity | 20%~85%(Non-Condensing) |
| | Working Temperature | −10°C~60°C |
| | Storage Humidity | 0%~90%(Non-Condensing) |
| АРР | Support Mobile Phone | IPhone and Android smart phone |
| | APP Language | Chinese, Italian, German, French, Dutch, Portuguese, Japan ese, Spanish, Russian, English, Vietnamese |
| | Website | www.bluecam.cloud |
| Certification | CE, FCC | |
| Pack List | Color Box | |
| | Power Supplier + USB Cable | |
| | Magnet Bracket | |
| | User Manual | |