

Model **QM1529**
Production **Auto Range Digital Multimeter**

| | Range | Accuracy |
|------------|------------------------------|-----------------|
| DC Voltage | 200mV/2V/20V/200V/500V | ±(0.8%+3) |
| AC Voltage | 2V/20V/200V/500V | ±(1.0%+10) |
| DC Current | 200µA/2mA/20mA/200mA/2A/10A | ±(1.0%+5) |
| AC Current | 200µA/2mA/20mA/200mA/2A/10A | ±(1.8%+5) |
| Resistance | 200Ω/2kΩ/20kΩ/200kΩ/2MΩ/20MΩ | ±(1.0%+2) |

| | |
|------------------|-----------------------|
| Max. Display | 2000 Counts |
| NCV Detection | Yes |
| LINE Test | Live Wire Recognition |
| Diode Test | Yes |
| Continuity Check | Yes |
| Data Hold | Yes |
| LCD Backlight | Yes |
| Auto Power Off | Yes |
| Overload Display | OL |

| | |
|-----------------------|----------------------|
| Max Input Voltage | 600VDC |
| Operating Temperature | 0°C-40°C |
| Operating Humidity | <80%RH |
| Storage Temperature | -10°C-60°C |
| Storage Humidity | <70%RH |
| Power Supply | 1.5V AAA Battery x 2 |
| Product Size (mm) | 144x70x32mm |
| Product Weight (g) | 200g |
| Safety Rating | CAT III 600V |