



### Blade Fuse Block

- ▶ For ATC or ATO Blade fuses
- ▶ 6.3mm Quick connect terminal.

- ▶ Two 5.5mm diameter mounting holes for #10 screws.
- ▶ Transparent cover for dust & humid protection.

### SPECIFICATIONS:

- ▶ Maximum Amperage per circuit – 15 Amps
- ▶ Maximum voltage 32VDC
- ▶ Cover material – clear polycarbonate

- ▶ Maximum Amperage per block – 30~90 Amps
- ▶ Base material – Nylon PA-66 15% FIBER
- ▶ Terminal Material – Copper (Tin Plating)

PART NO.	DESCRIPTION	MAXIMUM LOAD	A Dim.	B Dim.	C Dim.	
			± 0.2	± 0.2	± 0.2	
CM-0462	4 Way ATC or ATO Blade Fuse Block	30 Amps	82.1	64.5	48.8	
CM-0662	6 Way ATC or ATO Blade Fuse Block	45 Amps	101.9	84.8	69.1	
CM-0862	8 Way ATC or ATO Blade Fuse Block	60 Amps	121.9	105.2	88.8	
CM-1062	10 Way ATC or ATO Blade Fuse Block	90 Amps	142.2	125.6	108.9	
尺寸依據圖示數字 DONIT SCALE DRAWING		單位 UNIT	mm	一般公差 TOLERANCE CLASS	± 0.2	* 工程承認圖面 *