





| | POS.1 | POS.2 |
|-----------------|---|--|
| SWITCH FUNCTION |  ON |  MOM |
| Term. Comm. | 2-1 | 2-3 |
| SCHEMATIC |  |  |

| CONTACT PLATING | TERMINAL PLATING | RATINGS |
|------------------|------------------|---|
| Gold over silver | Gold over silver | 3 Amps @120 VAC or 28VDC 1 Amps @250 VAC |

SPECIFICATIONS

MECHANICAL LIFE: 50,000 make-and-break cycles.
CONTACT RESISTANCE: 20 mΩ max. initial @ 2-4VDC 100mA
INSULATION RESISTANCE: 1,000 MΩ min.
DIELECTRIC STRENGTH: 1,000 Vrms min.@sea level.
OPERATING TEMPERATURE: -30°C to 85°C.

MATERIALS

CASE & BUSHING - Glass filled nylon 66, flame retardand, heat stabilized (UL94V-0).
PLUNGER - Thermoplastic Polyester (UL 94V-0), with intenal O-ring seal.
SWITCH SUPPORT - Brass or steel electrotin plated.
CONTACT/TERMINAL - Copper alloy, with gold over silver

| SCALE (比例) : 3 : 2 | TITLE 圖名 | Sealed Sub - Miniature Pushbutton Switches | SIZE 圖紙 | A4 |
|---|---------------|--|------------|------------|
| TOLERANCE (公差) : 0.00 mm ± 0.25mm 0.0 mm ± 0.40mm ANGULAR : ± 5° | DWG NO. 圖號 | SP0380 | UNIT 單位 | inch mm |