


WB1754

PRODUCT SPECIFICATION

TYPE:	18AWG×2C SPEAKER CABLE	PART NO.:	3070700018			
SPEC.:	(41/0.160BC+PVC2.3) *2C+PVC6.0					
STANDARD:	REFER UL758& OUR CABLE STANDARD INSTRUCTURE					
CONSTRUCTION:						
CONDUCTOR	CONSTRUCTION	41/0.16 mm BC OFC)				
	DC RESISTANCES (MAX. at 20°C)	23.06 Ω/km				
INSULATION	MATERIAL / COLOUR	PVC /BK、RD,				
	DIAMETER / THICKNESS	2.3±0.10 mm / 0.56±0.10 mm				
FILLER	MATERIAL	/				
DRAIN WIRE	CONSTRUCTION	/				
WRAP	MATERIAL	/				
SHIELD	CONSTRUCTION	/				
	COVERAGE	/ %				
COVERING	MATERIAL / COLOUR	/				
	DIAMETER / THICKNESS	/				
JACKET	MATERIAL / COLOUR	PVC / BLACK				
	DIAMETER / THICKNESS	6.0±0.15 mm / 0.7±0.10 mm				
MARKING	HIGH PERFORMANCE 18AWG SPEAKER CABLE					
PERFORMNCE						
PHRSICAL PROPERTIES	INSULATIO N	SWING TEST	/	JACKET	SWING TEST	≥1500
		TENSILE STRENGTH (Mpa)	≥10.5		TENSILE STRENGTH (Mpa)	≥10.5
		ELONGAFGION	≥150%		ELONGAFGION	≥150%
EIECFRICAL PERFORMANCE	CAPACITANCE 工作电容 pF/m		/	VOITAGE (V/DC)		300
	CHARACTERISTIC IMPEDANCE 特性阻抗 Ω		/	WITHSTAND VOLTAGE (KV AC/MIN)		1.5
	FREQUEN 频率 MHZ		/	ATTENUATION (DB/M)		/
DRAWING				制作:	曾小斌 2012-05-23	
				审核:		
				批准:		